



| Туре | | | Certificate No: STAS/24/052/DM110/11/MODEL E | | | |
|------|--|--|--|---------------------------|-----------------------------|--|
| | Approval Certi | Date: 28 April 2025 | | | | |
| | | | | • | | |
| Α | Certificate Holder: | | | | | |
| | CALA Homes Ltd Adam House, 5 Mid New Cutlins, Edinburgh EH11 4DU | | | | | |
| | E-mail: SKelso@Cala.co.uk | , _a | | Tel: 0131 453 0072 | | |
| | T T 14 | | | | | |
| В | Type Title: Description: MODEL E | – BLOCK DA3 | | | | |
| | | - BLUCK DAS | | | | |
| С | The domestic type approval has been | assessed on the following dr | awings and specificat | ions: | | |
| | See attached ar | nnexe to this certificate | | | | |
| D | Climatic conditions: The design may | , be built in areas where the | climatic conditions are | equal to or less than the | se detailed below: | |
| D | | | | | se detailed below. | |
| | Wind: (as defined in BS 6399-2) | Standard effective wind spe | | | 24.5 m/s | |
| | | For maximum effective heig Has funnelling been consid | | | 16m to ridge No | |
| | | | | | | |
| | Wind: (as defined in CP3: Chapter V) | Design wind speed, Vs = (relevant to the building fra | ma at a baight of 3m | orlass) | 24.5m/s | |
| | v) | | ine, at a neight of on | | | |
| | Snow: (as defined in BS 6399-3) | Site snow load, So = | | YY | 0.75 kN/m2 | |
| | | Influenced by adjacent buil | aings? | | No | |
| | Resistance to moisture/durability | Max exposure (to wind driv | | | Exposure Zones 1, 2, 3 and | |
| | of exposed elements: | Thermal Insulation: Avoidir exposure zone: | ng Risks, Second Edit | ion, 1994, to be | 4 | |
| | | Exposure to sea spray (i.e. | coastal region) or de | -icing salts? | No | |
| | | Other air contaminants or t | piological factors – ple | ase specify any | None | |
| | | enhanced resistance if app | licable (refer to BS75 | 43 for guidance) | | |
| | Design Life: (per BS 7543 – | Category of building design life = | | | 60 years | |
| | Durability of buildings and building elements, products and | Design life of primary build | ing envelope | | 60 years | |
| | components) | Design life of primary building envelope 60 years | | | | |
| | | | | | | |
| E | Conditions of certification: 1. The design shown and the specific terms of the specific terms of the specific terms of the specific terms of te | cifications and materials refe | rred to have been as | sessed and approved in a | coordance with the Building | |
| | (Scotland) Regulations 2004 a | | | | | |
| | force with effect from 1 Januar | ry 2025. | | | | |
| | The certificate shall be valid until invalidated by formal notice by the Scottish Building Standards Hub. The design shown and the materials specified shall not be changed without reference to the Scottish Building Standards Hub who a | | | | | |
| | responsible for certifying the s | | changed without relen | | | |
| | Where reference is made on a plan or specification document to any Code of Practice, British or European Standard or manufacturer's instruction it shall be construed as a reference to such publication in the form in which it is in force at the date of this certificate. This certificate should not be regarded as a formal approval under the building warrant process prescribed by the Building (Scotland) Act 2003 enacted from 1 May 2005. | | | | | |
| | | | | | | |
| | | | | | | |
| | | burgh) Limited Statement of Structural Adequacy referenced here under Section G, confirm that a structural | | | | |
| | Pappraisal has been carried out. It is a requirement of this certificate that site-specific information MUST BE made available when a specific building warrant is sought. Such additional information should take cognisance of Procedural Guidance on Certification in | | | | | |
| | | information to be submitted with a Building Warrant Application dated April 2010 Version 2 (January 2017). Confirmation of a holistic approach to structural adequacy of the <u>entire completed building</u> shall be provided by a registered engineer to the local authority within whose area the site-specific dwelling is to be built. | | | | |
| | approach to structural adequa | | | | | |
| | | | | | | |
| | this standard will be submitted | | | | monotrate compliance within | |
| | 8. Site specific elements, such as | | | | nnection etc, require to be | |
| | assessed by the verifier. This certificate should be read | with the related certificates 9 | TAS/24/052/DM110/ | SD/MODELE STAS/24/0 | 52/DM110/SS/MODEL F and | |
| | STAS/24/052/DM110/UCR/MC | | | | | |
| | 31A3/24/U32/UWITIV/UUK/MUUDELE. | | | | | |





| F | Document Number | Revision | Description | | | |
|---|---------------------------------|----------|--|--|--|--|
| | CALA | | | | | |
| | DA3-WD1.1 | В | GROUND FLOOR PLAN | | | |
| | DA3-WD1.2 | | FIRST FLOOR PLAN | | | |
| | DA3-WD1.3 | | SECOND FLOOR PLAN | | | |
| | DA3-WD2.1 | | UNDERBUILDING LAYOUT - SUSPENDED SLAB | | | |
| | DA3-WD2.2 | | ROOF PLAN AND SECTION A-A - PITCHED ROOF | | | |
| | DA3-WD2.3 | | ROOF PLAN AND SECTION A-A - FLAT ROOF | | | |
| | DA3-WD6 | | STAIRS - PLANS AND SECTION | | | |
| | | | | | | |
| | HARLEY HADDOW | | | | | |
| | 314164-HAH-DA3-SC-D- S-00110 | P01 | STAIR CORE DA3 – LEVEL 0-LEVEL 1 FLOOR LAYOUTS | | | |
| | 314164-HAH-DA3-SC-D- S-00111 | P01 | STAIR CORE DA3 – LEVEL 2 FLOOR LAYOUT | | | |
| | 314164-HAH-DA3-SC-D- S-00112 | P01 | STAIR CORE DA3 – ROOF LAYOUT | | | |
| | 314164-HAH-DA3-SC-D- S-00113 | P02 | STAIR CORE DA3 – DETAILS | | | |

Annexe of drawings, certificates and specification documents used in the assessment:

| G | Certification |
|---|---------------|
| | |

CALA Homes Light and Space Model E Flats Statement of Structural Adequacy

Hai

2Pr

| | arley Ha | ddow (| Edinbur | 'gh) L | td da | ated | 24 J | June | 2024 |
|--|----------|--------|---------|--------|-------|------|------|------|------|
|--|----------|--------|---------|--------|-------|------|------|------|------|

| Н | Specification | |
|---|--|--------------------------------|
| | Astute Fire Strategy Report | Revision 4 - 14.04.25 |
| | Refer to STAS/24/052/DM110/SD/MODEL E | Standard Details |
| | Refer to STAS/24/052/DM110/SS/MODEL E | Standard Specifications |
| | Refer to STAS/24/052/DM110/UCR/MODEL E | U-values and Condensation Risk |
| | | |

Authority:

This system type approval certificate consisting of 2 pages is authorised by the Scottish Building Standards Hub on behalf of the Local Authority Building Standards Scotland (LABSS).